

MATERIAL SAFETY 3M
 DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
 All rights reserved. Copying and/or downloading of this
 information for the purpose of properly utilizing 3M products
 is allowed provided that:
 1) the information is copied in full with no changes unless
 prior agreement is obtained from 3M, and
 2) neither the copy nor the original is resold or otherwise
 distributed with the intention of earning a profit thereon.

DIVISION: MARINE TRADES PROJECT
 TRADE NAME:

3M(TM) Marine Metal Restorer and Polish, P.N. 09018, 09019; 3M(TM)
 Marine Metal Restorer and Polish Clip Strip Display, P.N. 09072

ID NUMBER/U.P.C.:

60-9800-2031-1 00-51131-09018-7 60-9800-2032-9 00-51131-09019-4
 60-9800-2594-8 00-51131-09019-4 60-9800-2595-5 00-51131-09019-4
 60-9800-3464-3 00-51131-09018-7 60-9800-3551-7 00-51131-16897-8
 60-9800-3552-5 00-51131-09019-4 60-9800-3681-2 00-51131-09072-9
 60-9800-3691-1 00-51131-16897-8

ISSUED: December 13, 2001
 SUPERSEDES: January 07, 2000
 DOCUMENT: 06-3267-9

1. INGREDIENT	C.A.S. NO.	PERCENT	
WATER.....	7732-18-5	30.0	- 60.0
ALUMINUM OXIDE.....	1344-28-1	30.0	- 60.0
HYDROTREATED LIGHT PETROLEUM DISTILLATES.....	64742-47-8	10.0	- 30.0
OLEIC ACID.....	112-80-1	5.0	- 10.0
AMMONIUM HYDROXIDE.....	1336-21-6	1.0	- 5.0
STEARAMIDE DEA.....	93-82-3	1.0	- 5.0

The components of this product are in compliance with the chemical
 notification requirements of TSCA. All applicable chemical
 ingredients in this material are listed on the European Inventory of
 Existing Chemical Substances (EINECS), or are exempt polymers whose
 monomers are listed on EINECS.

For technical service and product information/support, call
 1-877-366-2746 (1-877-3M MARINE).

This product contains the following toxic chemical or chemicals subject to
 the reporting requirements of Section 313 of Title III of the Emergency
 Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:
 AMMONIUM HYDROXIDE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA

BOILING POINT:..... 150 - 212 F
VAPOR PRESSURE:..... < 16 mmHg
VAPOR DENSITY:..... > 1.00 Air=1
EVAPORATION RATE:..... > 1 Water=1
SOLUBILITY IN WATER:..... moderate
SPECIFIC GRAVITY:..... 1.09 Water=1
PERCENT VOLATILE:..... 40 - 75 %
pH:..... ca. 9.4
VISCOSITY:..... N/D
MELTING POINT:..... N/D

APPEARANCE AND ODOR:
Paste, slight ammonia, pink.

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... > 220 F
FLAMMABLE LIMITS - LEL:..... N/D
FLAMMABLE LIMITS - UEL:..... N/D
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:
Water spray, Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:
Wear full protective clothing, including helmet, self-contained,
positive pressure or pressure demand breathing apparatus, bunker coat
and pants, bands around arms, waist and legs, face mask, and
protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
None known.

NFPA HAZARD CODES: HEALTH: 1 FIRE: 1 REACTIVITY: 0
UNUSUAL REACTION HAZARD: none

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:
Strong Oxidizing Agents.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

4. REACTIVITY DATA (continued)

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Toxic Vapors, Gases or
Particulates.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding
physical and health hazards, respiratory protection, ventilation, and
personal protective equipment. Extinguish all ignition sources.
Cover with absorbent material. Collect spilled material. Clean up
residue with water. Place in a U.S. DOT-approved container.

RECOMMENDED DISPOSAL:

Incinerate in an industrial or commercial facility in the presence of
a combustible material.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 1.63 lb/gal calculated per SCAQMD rule 443.1.
Volatile Organic Compounds: 196 gms/liter calculated per SCAQMD rule
443.1.
VOC Less H2O & Exempt Solvents: 328 gms/liter calculated per SCAQMD rule
443.1.

Since regulations vary, consult applicable regulations or authorities
before disposal. U.S. EPA Hazardous Waste Number = None (Not U.S.
EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: No

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate
medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get
medical attention.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

6. SUGGESTED FIRST AID (continued)

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact. Wear vented goggles.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: neoprene, nitrile rubber.

RECOMMENDED VENTILATION:

Provide appropriate local exhaust for grinding, cutting or sanding cured material. Provide appropriate local exhaust ventilation on open containers. Use in a well-ventilated area. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid prolonged breathing of vapors. Avoid breathing of dust created by cutting, sanding or grinding. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half-mask organic vapor respirator with dust/mist prefilter.

PREVENTION OF ACCIDENTAL INGESTION:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Wash hands after handling and before eating. Do not ingest.

RECOMMENDED STORAGE:

Store at temperatures above 32 degrees F (0 degrees C). Store out of direct sunlight. Keep container closed when not in use. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

 7. PRECAUTIONARY INFORMATION (continued)

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
WATER.....	NONE	NONE	NONE	NONE	
ALUMINUM OXIDE.....	1.0	FIBER/CC	TWA	CMRG	
ALUMINUM OXIDE.....	1.0	FIBER/CC	TWA	OSHA	
		PROPOSED			
ALUMINUM OXIDE.....	10	MG/M3	TWA	OSHAV	
		AS DUST			
		OSHA VACATED PEL			
ALUMINUM OXIDE.....	10	MG/M3	TWA	ACGIH	
		as Al			
ALUMINUM OXIDE.....	15	MG/M3	TWA	OSHA	
		AS TOTAL DUST			
ALUMINUM OXIDE.....	5	MG/M3	TWA	OSHA	
		RESPIRABLE			
HYDROTREATED LIGHT PETROLEUM DISTILLATES.....	300	PPM	TWA	CMRG	
OLEIC ACID.....	10	MG/M3	TWA	OSHA	
		AS MIST			
OLEIC ACID.....	10	MG/M3	TWA	ACGIH	
		AS MIST			
AMMONIUM HYDROXIDE.....	35	PPM	STEL	CMRG	
		AS AMMONIA			
AMMONIUM HYDROXIDE.....	25	PPM	TWA	CMRG	
		AS AMMONIA			
STEARAMIDE DEA.....	NONE	NONE	NONE	NONE	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL. Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.
- NONE: None Established

 Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

SKIN CONTACT:

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

INHALATION:

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system.

Prolonged or repeated overexposure, above recommended guidelines, may cause:

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

IF SWALLOWED:

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue, blurred vision, slurred speech, giddiness, tremors and convulsions.

SECTION CHANGE DATES

SUGG. FIRST AID	SECTION CHANGED SINCE	January 07, 2000	ISSUE
PRECAUTIONARY INFO.	SECTION CHANGED SINCE	January 07, 2000	ISSUE
HEALTH HAZARD DATA	SECTION CHANGED SINCE	January 07, 2000	ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.