

MATERIAL SAFETY 3M
 DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
 All rights reserved. Copying and/or downloading of this
 information for the purpose of properly utilizing 3M products
 is allowed provided that:
 1) the information is copied in full with no changes unless
 prior agreement is obtained from 3M, and
 2) neither the copy nor the original is resold or otherwise
 distributed with the intention of earning a profit thereon.

DIVISION: MARINE TRADES PROJECT
 TRADE NAME:

3M(TM) Marine Adhesive Sealant 5200 - Black, PN 05205, 05207, 06504,
 06504E, 06604

ID NUMBER/U.P.C.:

60-9800-2007-1 00-51135-06604-1 60-9800-2009-7 00-51135-05205-1
 60-9800-2011-3 00-51135-05207-5 60-9800-2071-7 00-51135-06504-4
 60-9800-2615-1 00-51135-06504-4 60-9800-2616-9 00-51131-46814-6
 60-9800-3254-8 00-51135-06504-4 60-9800-4305-7 00-51135-05205-1

ISSUED: May 29, 2001

SUPERSEDES: April 23, 2001

DOCUMENT: 11-6627-1

1. INGREDIENT	C.A.S. NO.	PERCENT	
URETHANE PREPOLYMER.....	57451-08-8	40.0	- 50.0
LIMESTONE.....	1317-65-3	30.0	- 40.0
CARBON BLACK.....	1333-86-4	1.0	- 10.0
ZINC OXIDE.....	1314-13-2	1.0	- 10.0
HEPTANE.....	142-82-5		< 0.2
TOLUENE DIISOCYANATE.....	26471-62-5		< 0.1

This product contains the following toxic chemical or chemicals subject to
 the reporting requirements of Section 313 of Title III of the Emergency
 Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

ZINC OXIDE
 TOLUENE DIISOCYANATE

2. PHYSICAL DATA

BOILING POINT:..... N/A
 VAPOR PRESSURE:..... N/A
 VAPOR DENSITY:..... N/A
 EVAPORATION RATE:..... N/A
 SOLUBILITY IN WATER:..... nil
 SPECIFIC GRAVITY:..... ca. 1.13 Water=1
 PERCENT VOLATILE:..... < 0.5 % by wt
 pH:..... N/A

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA (continued)

VISCOSITY:..... ca. 100000.0 centipoise
(Thixotropic paste)
MELTING POINT:..... N/D

APPEARANCE AND ODOR:
Thixotropic paste, black, very slight odor

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... 152 F PMCC
FLAMMABLE LIMITS - LEL:..... N/D
FLAMMABLE LIMITS - UEL:..... N/D
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:
Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:
Wear full protective clothing, including helmet, self-contained,
positive pressure or pressure demand breathing apparatus, bunker coat
and pants, bands around arms, waist and legs, face mask, and
protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
None known.

NFPA HAZARD CODES: HEALTH: 1 FIRE: 0 REACTIVITY: 0
UNUSUAL REACTION HAZARD: none

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:
Not determined

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:
Carbon Monoxide and Carbon Dioxide, Oxides of Nitrogen, Hydrogen
Cyanide.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Ventilate area. Contain spill. Evacuate unprotected personnel from hazard area. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Alternatively, pour water on spill and allow to react for more than 30 minutes. Cover with absorbent. Place in an approved drum, but do not seal the drum for 48 hours to avoid possible pressure buildup. Neutralize spill residue with decontaminant solution.

RECOMMENDED DISPOSAL:

Cure product according to product instructions. Dispose of completely cured (or polymerized) material in a sanitary landfill. Disposal alternative: Incinerate in an industrial or commercial facility in the presence of a combustible material.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 0.01 lb/gal calculated.
Volatile Organic Compounds: 2 gms/liter calculated per SCAQMD rule 443.1.
VOC Less H2O & Exempt Solvents: 2 gms/liter calculated per SCAQMD rule 443.1.

Since regulations vary, consult applicable regulations or authorities before disposal. In the event of an uncontrolled release of this material, the user should determine if the release qualifies as a reportable quantity. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Immediately wash skin with soap and large amounts of water. Remove contaminated clothing. If signs/symptoms occur, call a physician. Wash contaminated clothing before reuse and dispose of contaminated shoes.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

6. SUGGESTED FIRST AID (continued)

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact. Wear safety glasses with side shields.

SKIN PROTECTION:

Wear appropriate gloves when handling this material. Use one or more of the following personal protection items as necessary to prevent skin contact: apron, coveralls.

RECOMMENDED VENTILATION:

Use with appropriate local exhaust ventilation. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of vapors. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask supplied air respirator, full-face supplied air respirator.

PREVENTION OF ACCIDENTAL INGESTION:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

RECOMMENDED STORAGE:

Keep container dry. Keep container closed when not in use. Keep container in well-ventilated area. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition.

OTHER PRECAUTIONARY INFORMATION:

Do not use heat to aid in the removal of 5200 Marine Sealant. The application of heat may generate levels of Toluene Diisocyanate (TDI) in excess of the TLV.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

 7. PRECAUTIONARY INFORMATION (continued)

HMIS HAZARD RATINGS: HEALTH: 2 FLAMMABILITY: 0 REACTIVITY: 0
 PERSONAL PROTECTION: H

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
URETHANE PREPOLYMER.....	NONE	NONE	NONE	NONE	
LIMESTONE.....	10	MG/M3	TWA	ACGIH	
LIMESTONE.....	15	MG/M3	TWA	OSHA	
	AS TOTAL DUST				
LIMESTONE.....	5	MG/M3	TWA	OSHA	
	RESPIRABLE				
CARBON BLACK.....	3.5	MG/M3	TWA	ACGIH	
CARBON BLACK.....	3.5	MG/M3	TWA	OSHA	
CARBON BLACK.....	0.5	MG/M3	TWA	CMRG	
ZINC OXIDE.....	10	MG/M3	TWA	ACGIH	
	AS DUST				
ZINC OXIDE.....	10	MG/M3	TWA	OSHAV	
	AS DUST				
	OSHA VACATED PEL				
ZINC OXIDE.....	5	MG/M3	TWA	ACGIH	
	as fume				
ZINC OXIDE.....	10	MG/M3	STEL	ACGIH	
	as fume				
ZINC OXIDE.....	5	MG/M3	TWA	OSHA	
	as fume				
ZINC OXIDE.....	10	MG/M3	STEL	OSHAV	
	as fume				
	OSHA VACATED PEL				
ZINC OXIDE.....	15	MG/M3	TWA	OSHA	
	AS TOTAL DUST				
ZINC OXIDE.....	5	MG/M3	TWA	OSHA	
	RESPIRABLE				
HEPTANE.....	400	PPM	TWA	ACGIH	
HEPTANE.....	500	PPM	STEL	ACGIH	
HEPTANE.....	400	PPM	TWA	OSHAV	
	OSHA VACATED PEL				
HEPTANE.....	500	PPM	STEL	OSHAV	
	OSHA VACATED PEL				
HEPTANE.....	500	PPM	TWA	OSHA	
TOLUENE DIISOCYANATE.....	0.005	PPM	TWA	3M	
TOLUENE DIISOCYANATE.....	0.02	PPM	STEL	3M	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

 Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
------------	-------	------	------	------	-------

SOURCE OF EXPOSURE LIMIT DATA:

- 3M: 3M Recommended Exposure Guidelines
- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL.
Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.
- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

SKIN CONTACT:

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

Prolonged or repeated exposure may cause:

Allergic Skin Reaction: signs/symptoms can include redness, swelling, blistering, and itching.

INHALATION:

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

Prolonged or repeated exposure may cause:

Allergic Respiratory Reaction: signs/symptoms can include difficulty breathing, wheezing, tightness of chest, and respiratory failure.

IF SWALLOWED:

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

CANCER:

WARNING: Contains a chemical which can cause cancer. (1333-86-4)
(IARC possible human carcinogen 2B)

WARNING: Contains a chemical which can cause cancer. (26471-62-5)
(NTP anticipated human carcinogen, IARC possible human carcinogen 2B,
Calif. Proposition 65)

OTHER HEALTH HAZARD INFORMATION:

TOLUENE DIISOCYANATE (26471-62-5): Persons previously sensitized to
TDI or other isocyanate may react to subsequent exposures of
concentrations well below the TLV. These symptoms which can include
chest tightness, wheezing, cough, shortness of breath, or asthma
attack, could be immediate or delayed for several hours.

SECTION CHANGE DATES

HEADING	SECTION CHANGED SINCE April 23, 2001	ISSUE
---------	--------------------------------------	-------

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.