

MATERIAL SAFETY 3M  
 DATA SHEET 3M Center  
 St. Paul, Minnesota  
 55144-1000  
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2000, Minnesota Mining and Manufacturing Company.  
 All rights reserved. Copying and/or downloading of this  
 information for the purpose of properly utilizing 3M products  
 is allowed provided that:  
 1) the information is copied in full with no changes unless  
 prior agreement is obtained from 3M, and  
 2) neither the copy nor the original is resold or otherwise  
 distributed with the intention of earning a profit thereon.

DIVISION: AUTOMOTIVE AFTERMARKET  
 TRADE NAME:  
 3M brand 4 Way Spray Lubricant P/N 08902, 08898  
 ID NUMBER/U.P.C.:  
 60-9800-1897-6 00-51135-08898-2 62-4608-4919-3 00-51135-08902-6  
 ISSUED: October 24, 2000  
 SUPERSEDES: October 05, 2000  
 DOCUMENT: 10-3318-2

1. INGREDIENT	C.A.S. NO.	PERCENT
STODDARD SOLVENT.....	8052-41-3	30.0 - 50.0
KEROSENE.....	8008-20-6	10.0 - 20.0
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE (PETROLEUM).....	64742-65-0	10.0 - 20.0
ISOBUTANE.....	75-28-5	10.0 - 20.0
PROPANE.....	74-98-6	10.0 - 20.0
2-BUTOXYETHANOL.....	111-76-2	1.0 - 5.0

The components of this product are in compliance with the chemical notification requirements of TSCA. All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:  
 2-BUTOXYETHANOL

2. PHYSICAL DATA

BOILING POINT:.....	Compressed gas
VAPOR PRESSURE:.....	Compressed gas
VAPOR DENSITY:.....	> 3.00 Air=1
EVAPORATION RATE:.....	> 1.00 Ether=1
SOLUBILITY IN WATER:.....	Nil
SPECIFIC GRAVITY:.....	0.720 Water=1

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
2. PHYSICAL DATA (continued)  
-----

PERCENT VOLATILE:..... 86.00 % by wt  
pH:..... N/A  
VISCOSITY:..... N/A  
MELTING POINT:..... N/D

APPEARANCE AND ODOR:

Liquid in aerosol container, clear, straw colored.

-----  
3. FIRE AND EXPLOSION HAZARD DATA  
-----

FLASH POINT:..... -50.00 F  
FLAMMABLE LIMITS - LEL:..... N/A  
FLAMMABLE LIMITS - UEL:..... Flammable Gas  
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:

Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 4 REACTIVITY: 0  
UNUSUAL REACTION HAZARD: none

-----  
4. REACTIVITY DATA  
-----

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

Heat.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Toxic Vapors, Gases or Particulates.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
5. ENVIRONMENTAL INFORMATION  
-----

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Ventilate area. Extinguish all ignition sources. Cover with absorbent material. Collect using non-sparking tools. Place in a U.S. DOT-approved container.

RECOMMENDED DISPOSAL:

Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. Facility must be capable of handling aerosol cans. Dispose of empty cans in a sanitary landfill. Dispose of completely absorbed waste product in a facility permitted to accept chemical wastes.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 619 gms/liter South Coast Air Quality Mgmt Dist Method Rule 443.1, calculated.

VOC Less H2O & Exempt Solvents: 619 gms/liter South Coast Air Quality Mgmt Dist Method Rule 443.1, calculated.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = D001 (Ignitable)

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: Yes REACTIVITY: No ACUTE: Yes CHRONIC: Yes

-----  
6. SUGGESTED FIRST AID  
-----

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
7. PRECAUTIONARY INFORMATION  
-----

EYE PROTECTION:

Avoid eye contact with vapor, spray, or mist. Wear vented goggles.  
Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact. Wear appropriate gloves  
when handling this material. A pair of gloves made from the  
following material(s) are recommended: nitrile rubber,  
polyethylene/ethylene vinyl alcohol, polytetrafluoroethylene  
(Teflon).

RECOMMENDED VENTILATION:

Use in a well-ventilated area. Provide sufficient ventilation to  
maintain emissions below recommended exposure limits.

RESPIRATORY PROTECTION:

Avoid breathing of vapors, mists or spray.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Store at temperatures below 120 degrees F (49 degrees C). Keep out  
of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Aerosol container contains flammable gas under pressure. Keep away  
from heat, sparks, open flame, and other sources of ignition.  
Extremely flammable liquid and vapor. Do not pierce or burn  
container, even after use. Avoid static discharge.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
STODDARD SOLVENT.....	100	PPM	TWA	ACGIH	
STODDARD SOLVENT.....	100	PPM	TWA	OSHAV	
STODDARD SOLVENT.....	500	PPM	TWA	OSHA	
KEROSENE.....	500	PPM	TWA	CMRG	
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE (PETROLEUM).....	5	MG/M3	TWA	CMRG	
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE (PETROLEUM).....	10	MG/M3	STEL	CMRG	
ISOBUTANE.....	NONE	NONE	NONE	NONE	
PROPANE.....	1000	PPM	TWA	OSHA	
PROPANE.....	2500	PPM	TWA	ACGIH	
2-BUTOXYETHANOL.....	25	PPM	TWA	ACGIH	Y
2-BUTOXYETHANOL.....	25	PPM	TWA	OSHAV	Y
	OSHA VACATED PEL				

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
2-BUTOXYETHANOL.....	50	PPM	TWA	OSHA	Y

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL.  
Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.

- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

SKIN CONTACT:

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

INHALATION:

Intentional concentration and inhalation may be harmful or fatal.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Ingestion may cause:

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
8. HEALTH HAZARD DATA (continued)  
-----

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

-----  
SECTION CHANGE DATES  
-----

PRECAUTIONARY INFO. SECTION CHANGED SINCE October 05, 2000 ISSUE

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately  
-----

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.